

# FORKLIFT JACKS & STANDS

**TOTALSOURCE®**

FEATURED PRODUCTS

**SY15000**



- Meets CE requirements

Specifications	U.S. Units	Metric Units
Capacity	15,442LBS	7 mt
Power	Two-Speed Hydraulic Pump	
Min. starting height	2¼"	57mm
Max. lifting height	16"	406mm
Forward reach	7"	178mm
Width	9"	228mm
Shipping weight	92LBS	42kg

**SY8000**



- Meets CE requirements
- 2year limited warranty
- Replacement parts for old style Gray® (FLJ model jacks) also available
- Made in th U.S.A.

Specifications	U.S. Units	Metric Units
Capacity	8,000LBS	3.6mt
Start pad height (notch)	2.25"	57mm
Start pad height (serrated pad)	2.5"	63mm
Raised height (maximum)	16"	406mm
Width	8"	203mm
Weight	68LBS	30.6kg
Reach (raised position)	7"	117mm
(Distance from hydraulic cylinder to lift pad)		

**SY400**



- 4 position height adjustment
- Made in the U.S.A.
- Sold in pairs

Specifications	U.S. Units	Metric Units
Capacity	30,870LBS	13.9mt (pair)
Pad dimensions	2.5" x 3.5"	63mm x 89mm
Start pad height	9.5"	241mm
Raised height	16"	406mm
Height increments	2"	50mm
Weight (pair)	31LBS	14kg
Base	8"SQ	203mm

United States  
800 255 4109  
Fax 913 764 7278

International  
913 768 3099  
Fax 913 829 6206

Canada (ONT)  
800 509 7668  
Fax 905 564 5717

Canada (BC)  
888 661 8611  
Fax 604 944 7024

Mexico  
+52 55 5861 8550  
Fax +52 55 5819 3004